

# OTTOSEAL M 390



C01  
weiß/white  
blanc/wit



C8180  
kieselgrau/pebble grey  
gris galet/kieselgrijs



C56  
betongrau/concrete grey  
gris béton/betongrijs



C1172  
titangrau/titan grey  
gris titane/titaangrijs



C2260  
basalt/basalt  
basalte/basalt



C10  
bahamabeige/bahamabeige  
bahamabeige/bahamabeige



C105  
eiche hell/fair oak  
chêne, Kiefer, fichte, eur. ahorn/ash, pine, spruce, Eur. maple  
frêne, pin, sapin, érable eur./es, den, spar, Eur. ahorn



C64  
eiche hell/fair oak  
chêne éclatant/eik helder



C76  
buche/beech  
hêtre/beuk



C1237  
eiche dunkel/dark oak  
chêne foncé/eik donker



C17  
kirschbaum/cherry  
cerisier/kerselaar



C98  
eiche rustikal/rustic oak  
chêne rustique/eik rustikal



C49  
dunkelbraun/dark brown  
brun foncé/donkerbruin



OTTO  
SEAL®  
M 390

Hoch beanspruchbar



**Boden-Dichtstoff**  
Floor sealant  
Mastic de sol  
Vloerafdichtingskit

- ✓ Extrem elastisch
- ✓ Gute Chemikalienbeständigkeit
- ✓ Härtet praktisch schwindfrei aus

**OTTO**  
CHEMIE  
DICHTEN & KLEBEN

Colle  
OU Mastic

**OTTO**  
CHEMIE  
DICHTEN & KLEBEN